









BARGE: NGL 3016

HULL No. JEFFBOAT 14-2895

2 STBD  
INNAGE TABLE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 16' 1"

Table with 24 columns (0 FT. to 14 FT.) and 20 rows (0 to 11). Each cell contains capacity values for different gauging heights (1/4, 1/2, 3/4) and tank diameters (IN, 0). Values increase from ~14.80 to ~341.80 barrels across the length.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.  
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK - TRIM CORRECTION NOT REQUIRED.  
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL  
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPA

DATE STRAPPED: 10/4/926 BY: JMF  
DATE COMPUTED: 4/03/2015 BY: WHF  
DATE ISSUED: 4/04/2015

INTERTEK









CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 16' 1 1/4"

Table with columns for Ullage Height (0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16 FT.) and sub-columns for depth (IN, 1/4, 1/2, 3/4). Each cell contains capacity values in barrels.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES

DATE STRAPPED: 3/31/2015 BY: JMF

NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK - TRIM CORRECTION NOT REQUIRED.

OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE COMPUTED: 4/03/2015 BY: WHF

NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL

DATE ISSUED: 4/04/2015

NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7



CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 16' 2"

Table with columns for height (0 to 16 FT) and capacity (0 to 43.75 barrels). Rows are grouped by height intervals (0-1, 1-1.5, 1.5-2, 2-2.5, 2.5-3, 3-3.5, 3.5-4, 4-4.5, 4.5-5, 5-5.5, 5.5-6, 6-6.5, 6.5-7, 7-7.5, 7.5-8, 8-8.5, 8.5-9, 9-9.5, 9.5-10, 10-10.5, 10.5-11, 11-11.5, 11.5-12, 12-12.5, 12.5-13, 13-13.5, 13.5-14, 14-14.5, 14.5-15, 15-15.5, 15.5-16). Each cell contains capacity values for different gauge heights (0, 1/4, 1/2, 3/4).

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK - TRIM CORRECTION NOT REQUIRED.
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 3/31/2015 BY: JMF
DATE COMPUTED: 4/03/2015 BY: WHF
DATE ISSUED: 4/04/2015





CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 16' 1 1/4"

Table with columns for depth (0 to 16 FT.) and corresponding capacity values in barrels. The table is organized into 16 vertical sections, each representing a 1-foot depth interval. Each section contains 4 rows for different gauge heights: 0, 1/4, 1/2, and 3/4 feet. The capacity values generally increase with depth and decrease with gauge height.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.

NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK - TRIM CORRECTION NOT REQUIRED.

NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL

NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 3/31/2015 BY: JMF

DATE COMPUTED: 4/03/2015 BY: WHF

DATE ISSUED: 4/04/2015

INTERTEK

Handwritten signature of a representative.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 16' 1"

Table with columns for height (0 to 16 FT) and capacity (0 to 32.66 barrels). Rows are grouped by height intervals (0-1, 1-1.5, 1.5-2, 2-2.5, 2.5-3, 3-3.5, 3.5-4, 4-4.5, 4.5-5, 5-5.5, 5.5-6, 6-6.5, 6.5-7, 7-7.5, 7.5-8, 8-8.5, 8.5-9, 9-9.5, 9.5-10, 10-10.5, 10.5-11, 11-11.5, 11.5-12, 12-12.5, 12.5-13, 13-13.5, 13.5-14, 14-14.5, 14.5-15, 15-15.5, 15.5-16). Each cell contains capacity values for different gauge heights (0, 1/4, 1/2, 3/4).

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK - TRIM CORRECTION NOT REQUIRED.
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 3/31/2015 BY: JMF
DATE COMPUTED: 4/03/2015 BY: WHF
DATE ISSUED: 4/04/2015











## BARGE: NGL 3016

HULL No. JEFFBOAT 14-2895

## SLOP TANK PORT

### INNAGE TABLE

CAPACITIES GIVEN IN WHOLE U.S. GALLONS

GUAGE HEIGHT: 6' 5 1/4"

IN	0 FT.	IN	0 FT.	IN	1 FT.	IN	1 FT.	IN	2 FT.	IN	2 FT.	IN	3 FT.	IN	3 FT.	IN	4 FT.	IN	4 FT.	IN	5 FT.
0	1	6	361	0	924	6	1,487	0	2,050	6	2,612	0	3,175	6	3,738	0	4,301	6	4,864	0	0
1/8	2	1/8	373	1/8	936	1/8	1,499	1/8	2,061	1/8	2,624	1/8	3,187	1/8	3,750	1/8	4,312	1/8	4,875	1/8	
1/4	4	1/4	385	1/4	947	1/4	1,510	1/4	2,073	1/4	2,636	1/4	3,199	1/4	3,761	1/4	4,324	1/4	4,887	1/4	
3/8	5	3/8	396	3/8	959	3/8	1,522	3/8	2,085	3/8	2,648	3/8	3,210	3/8	3,773	3/8	4,336	3/8	4,899	3/8	
1/2	7	1/2	408	1/2	971	1/2	1,534	1/2	2,096	1/2	2,659	1/2	3,222	1/2	3,785	1/2	4,348	1/2	4,910	1/2	
5/8	9	5/8	420	5/8	983	5/8	1,545	5/8	2,108	5/8	2,671	5/8	3,234	5/8	3,797	5/8	4,359	5/8	4,922	5/8	
3/4	12	3/4	432	3/4	994	3/4	1,557	3/4	2,120	3/4	2,683	3/4	3,246	3/4	3,808	3/4	4,371	3/4	4,934	3/4	
7/8	14	7/8	443	7/8	1,006	7/8	1,569	7/8	2,132	7/8	2,694	7/8	3,257	7/8	3,820	7/8	4,383	7/8	4,946	7/8	
1	17	7	455	1	1,018	7	1,581	1	2,143	7	2,706	1	3,269	7	3,832	1	4,395	7	4,957	1	
1/8	21	1/8	467	1/8	1,030	1/8	1,592	1/8	2,155	1/8	2,718	1/8	3,281	1/8	3,843	1/8	4,406	1/8	4,969	1/8	
1/4	24	1/4	478	1/4	1,041	1/4	1,604	1/4	2,167	1/4	2,730	1/4	3,292	1/4	3,855	1/4	4,418	1/4	4,981	1/4	
3/8	28	3/8	490	3/8	1,053	3/8	1,616	3/8	2,179	3/8	2,741	3/8	3,304	3/8	3,867	3/8	4,430	3/8	4,993	3/8	
1/2	32	1/2	502	1/2	1,065	1/2	1,627	1/2	2,190	1/2	2,753	1/2	3,316	1/2	3,879	1/2	4,441	1/2	5,004	1/2	
5/8	37	5/8	514	5/8	1,076	5/8	1,639	5/8	2,202	5/8	2,765	5/8	3,328	5/8	3,890	5/8	4,453	5/8	5,016	5/8	
3/4	41	3/4	525	3/4	1,088	3/4	1,651	3/4	2,214	3/4	2,777	3/4	3,339	3/4	3,902	3/4	4,465	3/4	5,028	3/4	
7/8	46	7/8	537	7/8	1,100	7/8	1,663	7/8	2,225	7/8	2,788	7/8	3,351	7/8	3,914	7/8	4,477	7/8	5,039	7/8	
2	52	8	549	2	1,112	8	1,674	2	2,237	8	2,800	2	3,363	8	3,926	2	4,488	8	5,051	2	
1/8	57	1/8	561	1/8	1,123	1/8	1,686	1/8	2,249	1/8	2,812	1/8	3,375	1/8	3,937	1/8	4,500	1/8	5,063	1/8	
1/4	63	1/4	572	1/4	1,135	1/4	1,698	1/4	2,261	1/4	2,823	1/4	3,386	1/4	3,949	1/4	4,512	1/4	5,075	1/4	
3/8	69	3/8	584	3/8	1,147	3/8	1,710	3/8	2,272	3/8	2,835	3/8	3,398	3/8	3,961	3/8	4,524	3/8	5,086	3/8	
1/2	76	1/2	596	1/2	1,158	1/2	1,721	1/2	2,284	1/2	2,847	1/2	3,410	1/2	3,972	1/2	4,535	1/2	5,098	1/2	
5/8	82	5/8	607	5/8	1,170	5/8	1,733	5/8	2,296	5/8	2,859	5/8	3,421	5/8	3,984	5/8	4,547	5/8	5,110	5/8	
3/4	89	3/4	619	3/4	1,182	3/4	1,745	3/4	2,308	3/4	2,870	3/4	3,433	3/4	3,996	3/4	4,559	3/4	5,122	3/4	
7/8	97	7/8	631	7/8	1,194	7/8	1,756	7/8	2,319	7/8	2,882	7/8	3,445	7/8	4,008	7/8	4,570	7/8	5,133	7/8	
3	104	9	643	3	1,205	9	1,768	3	2,331	9	2,894	3	3,457	9	4,019	3	4,582	9	5,145	3	
1/8	112	1/8	654	1/8	1,217	1/8	1,780	1/8	2,343	1/8	2,906	1/8	3,468	1/8	4,031	1/8	4,594	1/8	5,157	1/8	
1/4	120	1/4	666	1/4	1,229	1/4	1,792	1/4	2,354	1/4	2,917	1/4	3,480	1/4	4,043	1/4	4,606	1/4	5,168	1/4	
3/8	129	3/8	678	3/8	1,241	3/8	1,803	3/8	2,366	3/8	2,929	3/8	3,492	3/8	4,055	3/8	4,617	3/8	5,180	3/8	
1/2	137	1/2	690	1/2	1,252	1/2	1,815	1/2	2,378	1/2	2,941	1/2	3,503	1/2	4,066	1/2	4,629	1/2	5,192	1/2	
5/8	146	5/8	701	5/8	1,264	5/8	1,827	5/8	2,390	5/8	2,952	5/8	3,515	5/8	4,078	5/8	4,641	5/8	5,204	5/8	
3/4	156	3/4	713	3/4	1,276	3/4	1,839	3/4	2,401	3/4	2,964	3/4	3,527	3/4	4,090	3/4	4,653	3/4	5,215	3/4	
7/8	165	7/8	725	7/8	1,287	7/8	1,850	7/8	2,413	7/8	2,976	7/8	3,539	7/8	4,101	7/8	4,664	7/8	5,227	7/8	
4	175	10	736	4	1,299	10	1,862	4	2,425	10	2,988	4	3,550	10	4,113	4	4,676	10	5,239	4	
1/8	185	1/8	748	1/8	1,311	1/8	1,874	1/8	2,437	1/8	2,999	1/8	3,562	1/8	4,125	1/8	4,688	1/8	5,250	1/8	
1/4	197	1/4	760	1/4	1,323	1/4	1,885	1/4	2,448	1/4	3,011	1/4	3,574	1/4	4,137	1/4	4,699	1/4	5,262	1/4	
3/8	209	3/8	772	3/8	1,334	3/8	1,897	3/8	2,460	3/8	3,023	3/8	3,586	3/8	4,148	3/8	4,711	3/8	5,274	3/8	
1/2	221	1/2	783	1/2	1,346	1/2	1,909	1/2	2,472	1/2	3,034	1/2	3,597	1/2	4,160	1/2	4,723	1/2	5,286	1/2	
5/8	232	5/8	795	5/8	1,358	5/8	1,921	5/8	2,483	5/8	3,046	5/8	3,609	5/8	4,172	5/8	4,735	5/8	5,297	5/8	
3/4	244	3/4	807	3/4	1,370	3/4	1,932	3/4	2,495	3/4	3,058	3/4	3,621	3/4	4,184	3/4	4,746	3/4	5,309	3/4	
7/8	256	7/8	818	7/8	1,381	7/8	1,944	7/8	2,507	7/8	3,070	7/8	3,632	7/8	4,195	7/8	4,758	7/8	5,321	7/8	
5	267	11	830	5	1,393	11	1,956	5	2,519	11	3,081	5	3,644	11	4,207	5	4,770	11	5,333	5	
1/8	279	1/8	842	1/8	1,405	1/8	1,968	1/8	2,530	1/8	3,093	1/8	3,656	1/8	4,219	1/8	4,781	1/8	5,345	1/8	
1/4	291	1/4	854	1/4	1,416	1/4	1,979	1/4	2,542	1/4	3,105	1/4	3,668	1/4	4,230	1/4	4,793	1/4	5,357	1/4	
3/8	303	3/8	865	3/8	1,428	3/8	1,991	3/8	2,554	3/8	3,117	3/8	3,679	3/8	4,242	3/8	4,805	3/8	5,369	3/8	
1/2	314	1/2	877	1/2	1,440	1/2	2,003	1/2	2,565	1/2	3,128	1/2	3,691	1/2	4,254	1/2	4,817	1/2	5,381	1/2	
5/8	326	5/8	889	5/8	1,452	5/8	2,014	5/8	2,577	5/8	3,140	5/8	3,703	5/8	4,266	5/8	4,828	5/8	5,393	5/8	
3/4	338	3/4	901	3/4	1,463	3/4	2,026	3/4	2,589	3/4	3,152	3/4	3,715	3/4	4,277	3/4	4,840	3/4	5,405	3/4	
7/8	349	7/8	912	7/8	1,475	7/8	2,038	7/8	2,601	7/8	3,163	7/8	3,726	7/8	4,289	7/8	4,852	7/8	5,417	7/8	

CAPACITY AT ZERO IS THE VOLUMES AT THE GAUGE POINT DUE TO TANK BOTTOM SLOPE.

DATE STRAPPED: 3/31/2015 BY: JMF  
 DATE COMPUTED: 4/03/2015 BY: WHF  
 DATE ISSUED: 4/04/2015

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

**INTERTEK**







# BARGE: NGL 3016

HULL No. JEFFBOAT 14-2895

# SLOP TANK PORT

## ULLAGE TABLE

CAPACITIES GIVEN IN WHOLE U.S. GALLONS

GAUGE HEIGHT: 6' 5 1/4"

IN	1 FT.	IN	1 FT.	IN	2 FT.	IN	2 FT.	IN	3 FT.	IN	3 FT.	IN	4 FT.	IN	4 FT.	IN	5 FT.	IN	5 FT.	IN	6 FT.
0		6		0	4,793	6	4,230	0	3,668	6	3,105	0	2,542	6	1,979	0	1,416	6	854	0	291
1/8		1/8		1/8	4,781	1/8	4,219	1/8	3,656	1/8	3,093	1/8	2,530	1/8	1,968	1/8	1,405	1/8	842	1/8	279
1/4		1/4		1/4	4,770	1/4	4,207	1/4	3,644	1/4	3,081	1/4	2,519	1/4	1,956	1/4	1,393	1/4	830	1/4	267
3/8		3/8	5,321	3/8	4,758	3/8	4,195	3/8	3,632	3/8	3,070	3/8	2,507	3/8	1,944	3/8	1,381	3/8	818	3/8	256
1/2		1/2	5,309	1/2	4,746	1/2	4,184	1/2	3,621	1/2	3,058	1/2	2,495	1/2	1,932	1/2	1,370	1/2	807	1/2	244
5/8		5/8	5,297	5/8	4,735	5/8	4,172	5/8	3,609	5/8	3,046	5/8	2,483	5/8	1,921	5/8	1,358	5/8	795	5/8	232
3/4		3/4	5,286	3/4	4,723	3/4	4,160	3/4	3,597	3/4	3,034	3/4	2,472	3/4	1,909	3/4	1,346	3/4	783	3/4	221
7/8		7/8	5,274	7/8	4,711	7/8	4,148	7/8	3,586	7/8	3,023	7/8	2,460	7/8	1,897	7/8	1,334	7/8	772	7/8	209
1		7	5,262	1	4,699	7	4,137	1	3,574	7	3,011	1	2,448	7	1,885	1	1,323	7	760	1	197
1/8		1/8	5,250	1/8	4,688	1/8	4,125	1/8	3,562	1/8	2,999	1/8	2,437	1/8	1,874	1/8	1,311	1/8	748	1/8	185
1/4		1/4	5,239	1/4	4,676	1/4	4,113	1/4	3,550	1/4	2,988	1/4	2,425	1/4	1,862	1/4	1,299	1/4	736	1/4	175
3/8		3/8	5,227	3/8	4,664	3/8	4,101	3/8	3,539	3/8	2,976	3/8	2,413	3/8	1,850	3/8	1,287	3/8	725	3/8	165
1/2		1/2	5,215	1/2	4,653	1/2	4,090	1/2	3,527	1/2	2,964	1/2	2,401	1/2	1,839	1/2	1,276	1/2	713	1/2	156
5/8		5/8	5,204	5/8	4,641	5/8	4,078	5/8	3,515	5/8	2,952	5/8	2,390	5/8	1,827	5/8	1,264	5/8	701	5/8	146
3/4		3/4	5,192	3/4	4,629	3/4	4,066	3/4	3,503	3/4	2,941	3/4	2,378	3/4	1,815	3/4	1,252	3/4	690	3/4	137
7/8		7/8	5,180	7/8	4,617	7/8	4,055	7/8	3,492	7/8	2,929	7/8	2,366	7/8	1,803	7/8	1,241	7/8	678	7/8	129
2		8	5,168	2	4,606	8	4,043	2	3,480	8	2,917	2	2,354	8	1,792	2	1,229	8	666	2	120
1/8		1/8	5,157	1/8	4,594	1/8	4,031	1/8	3,468	1/8	2,906	1/8	2,343	1/8	1,780	1/8	1,217	1/8	654	1/8	112
1/4		1/4	5,145	1/4	4,582	1/4	4,019	1/4	3,457	1/4	2,894	1/4	2,331	1/4	1,768	1/4	1,205	1/4	643	1/4	104
3/8		3/8	5,133	3/8	4,570	3/8	4,008	3/8	3,445	3/8	2,882	3/8	2,319	3/8	1,756	3/8	1,194	3/8	631	3/8	97
1/2		1/2	5,122	1/2	4,559	1/2	3,996	1/2	3,433	1/2	2,870	1/2	2,308	1/2	1,745	1/2	1,182	1/2	619	1/2	89
5/8		5/8	5,110	5/8	4,547	5/8	3,984	5/8	3,421	5/8	2,859	5/8	2,296	5/8	1,733	5/8	1,170	5/8	607	5/8	82
3/4		3/4	5,098	3/4	4,535	3/4	3,972	3/4	3,410	3/4	2,847	3/4	2,284	3/4	1,721	3/4	1,158	3/4	596	3/4	76
7/8		7/8	5,086	7/8	4,524	7/8	3,961	7/8	3,398	7/8	2,835	7/8	2,272	7/8	1,710	7/8	1,147	7/8	584	7/8	69
3		9	5,075	3	4,512	9	3,949	3	3,386	9	2,823	3	2,261	9	1,698	3	1,135	9	572	3	63
1/8		1/8	5,063	1/8	4,500	1/8	3,937	1/8	3,375	1/8	2,812	1/8	2,249	1/8	1,686	1/8	1,123	1/8	561	1/8	57
1/4		1/4	5,051	1/4	4,488	1/4	3,926	1/4	3,363	1/4	2,800	1/4	2,237	1/4	1,674	1/4	1,112	1/4	549	1/4	52
3/8		3/8	5,039	3/8	4,477	3/8	3,914	3/8	3,351	3/8	2,788	3/8	2,225	3/8	1,663	3/8	1,100	3/8	537	3/8	46
1/2		1/2	5,028	1/2	4,465	1/2	3,902	1/2	3,339	1/2	2,777	1/2	2,214	1/2	1,651	1/2	1,088	1/2	525	1/2	41
5/8		5/8	5,016	5/8	4,453	5/8	3,890	5/8	3,328	5/8	2,765	5/8	2,202	5/8	1,639	5/8	1,076	5/8	514	5/8	37
3/4		3/4	5,004	3/4	4,441	3/4	3,879	3/4	3,316	3/4	2,753	3/4	2,190	3/4	1,627	3/4	1,065	3/4	502	3/4	32
7/8		7/8	4,993	7/8	4,430	7/8	3,867	7/8	3,304	7/8	2,741	7/8	2,179	7/8	1,616	7/8	1,053	7/8	490	7/8	28
4		10	4,981	4	4,418	10	3,855	4	3,292	10	2,730	4	2,167	10	1,604	4	1,041	10	478	4	24
1/8		1/8	4,969	1/8	4,406	1/8	3,843	1/8	3,281	1/8	2,718	1/8	2,155	1/8	1,592	1/8	1,030	1/8	467	1/8	21
1/4		1/4	4,957	1/4	4,395	1/4	3,832	1/4	3,269	1/4	2,706	1/4	2,143	1/4	1,581	1/4	1,018	1/4	455	1/4	17
3/8		3/8	4,946	3/8	4,383	3/8	3,820	3/8	3,257	3/8	2,694	3/8	2,132	3/8	1,569	3/8	1,006	3/8	443	3/8	14
1/2		1/2	4,934	1/2	4,371	1/2	3,808	1/2	3,246	1/2	2,683	1/2	2,120	1/2	1,557	1/2	994	1/2	432	1/2	12
5/8		5/8	4,922	5/8	4,359	5/8	3,797	5/8	3,234	5/8	2,671	5/8	2,108	5/8	1,545	5/8	983	5/8	420	5/8	9
3/4		3/4	4,910	3/4	4,348	3/4	3,785	3/4	3,222	3/4	2,659	3/4	2,096	3/4	1,534	3/4	971	3/4	408	3/4	7
7/8		7/8	4,899	7/8	4,336	7/8	3,773	7/8	3,210	7/8	2,648	7/8	2,085	7/8	1,522	7/8	959	7/8	396	7/8	5
5		11	4,887	5	4,324	11	3,761	5	3,199	11	2,636	5	2,073	11	1,510	5	947	11	385	5	4
1/8		1/8	4,875	1/8	4,312	1/8	3,750	1/8	3,187	1/8	2,624	1/8	2,061	1/8	1,499	1/8	936	1/8	373	1/8	2
1/4		1/4	4,864	1/4	4,301	1/4	3,738	1/4	3,175	1/4	2,612	1/4	2,050	1/4	1,487	1/4	924	1/4	361	1/4	1
3/8		3/8	4,852	3/8	4,289	3/8	3,726	3/8	3,163	3/8	2,601	3/8	2,038	3/8	1,475	3/8	912	3/8	349	3/8	
1/2		1/2	4,840	1/2	4,277	1/2	3,715	1/2	3,152	1/2	2,589	1/2	2,026	1/2	1,463	1/2	901	1/2	338	1/2	
5/8		5/8	4,828	5/8	4,266	5/8	3,703	5/8	3,140	5/8	2,577	5/8	2,014	5/8	1,452	5/8	889	5/8	326	5/8	
3/4		3/4	4,817	3/4	4,254	3/4	3,691	3/4	3,128	3/4	2,565	3/4	2,003	3/4	1,440	3/4	877	3/4	314	3/4	
7/8		7/8	4,805	7/8	4,242	7/8	3,679	7/8	3,117	7/8	2,554	7/8	1,991	7/8	1,428	7/8	865	7/8	303	7/8	

CAPACITY AT ZERO IS THE VOLUMES AT THE GAUGE POINT DUE TO TANK BOTTOM SLOP  
SHADED AREA OF TABLE IS THE VOLUMES BELOW THE STRIKE POINT DUE TO CAMBERED BOTTC

DATE STRAPPED: 3/31/2015 BY: JMF  
DATE COMPUTED: 4/03/2015 BY: WHF  
DATE ISSUED: 4/04/2015

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES  
OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY

INTERTEK





BARGE: NGL 3016

HULL No. JEFFBOAT 14-2895

SLOP TANK STBD

ULLAGE TABLE

CAPACITIES GIVEN IN WHOLE U.S. GALLONS

GAUGE HEIGHT: 6' 4 3/4"

Table with 20 columns (IN, 1 FT., IN, 1 FT., IN, 2 FT., IN, 2 FT., IN, 3 FT., IN, 3 FT., IN, 4 FT., IN, 4 FT., IN, 5 FT., IN, 5 FT., IN, 6 FT.) and 43 rows (0, 1/8, 1/4, 3/8, 1/2, 5/8, 3/4, 7/8, 1, 1/8, 1/4, 3/8, 1/2, 5/8, 3/4, 7/8, 2, 1/8, 1/4, 3/8, 1/2, 5/8, 3/4, 7/8, 3, 1/8, 1/4, 3/8, 1/2, 5/8, 3/4, 7/8, 4, 1/8, 1/4, 3/8, 1/2, 5/8, 3/4, 7/8, 5, 1/8, 1/4, 3/8, 1/2, 5/8, 3/4, 7/8). It lists capacity values for various gauge heights from 0 to 5 feet.

CAPACITY AT ZERO IS THE VOLUMES AT THE GAUGE POINT DUE TO TANK BOTTOM SLOPE  
SHADED AREA OF TABLE IS THE VOLUMES BELOW THE STRIKE POINT DUE TO CAMBERED BOTTC

DATE STRAPPED: 3/31/2015 BY: JMF  
DATE COMPUTED: 4/03/2015 BY: WHF  
DATE ISSUED: 4/04/2015

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES  
OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY

INTERTEK

